

QUIKCOTE VELVET "DADDO" FINISH

Chemwatch GHS Safety Data Sheet
Issue Date: 26-Jul-2013
C554SP

CHEMWATCH 4951-17
Version No:6.1.1.1
CD 2013/2 Page 1 of 7

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

QUIKCOTE VELVET "DADDO" FINISH

PRODUCT USE

Used to achieve a fine smooth surface profile for exterior and interior applications on most masonry surfaces.

SUPPLIER

Company: QuikCote
Address:
26 - 30 Fleet Street
Somerton
VIC, 3062
Australia
Telephone: +61 3 9303 7791
Fax: +61 3 9303 7792

Section 2 - HAZARDS IDENTIFICATION

GHS Classification

Serious Eye Damage Category 1
Skin Corrosion/Irritation Category 2
STOT - SE Category 3



EMERGENCY OVERVIEW

HAZARD DANGER

Determined by Chemwatch using GHS criteria
H315 Causes skin irritation.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.

PRECAUTIONARY STATEMENTS

Prevention

Code	Phrase
P261	Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well- ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

Response

Code	Phrase
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.
P310	Call a POISON CENTER or doctor/physician if you feel unwell.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P362	Take off contaminated clothing and wash before re- use.

Storage

Code	Phrase
P403+P233	Store in a well- ventilated place. Keep container tightly closed.
P405	Store locked up.

Disposal

continued...

QUIKCOTE VELVET "DADDO" FINISH

Chemwatch GHS Safety Data Sheet
Issue Date: 26-Jul-2013
C554SP

CHEMWATCH 4951-17
Version No:6.1.1.1
CD 2013/2 Page 2 of 7
Section 2 - HAZARDS IDENTIFICATION

Code	Phrase
P501	Dispose of contents/container to authorised landfill.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
portland cement fillers, as calcium carbonate	65997-15-1	30-60
acrylic polymer	471-34-1	30-60
	Not avail.	10-30

Section 4 - FIRST AID MEASURES

SWALLOWED

- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.

EYE

- If this product comes in contact with the eyes:
- Wash out immediately with fresh running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- Seek medical attention without delay; if pain persists or recurs seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

- If skin contact occurs:
- Immediately remove all contaminated clothing, including footwear.
- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

INHALED

- If dust is inhaled, remove from contaminated area.
- Encourage patient to blow nose to ensure clear passage of breathing.
- If irritation or discomfort persists seek medical attention.

NOTES TO PHYSICIAN

- Treat symptomatically.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves in the event of a fire.
- Prevent, by any means available, spillage from entering drains or water courses.
- Use fire fighting procedures suitable for surrounding area.

FIRE/EXPLOSION HAZARD

- Non combustible.
- Not considered a significant fire risk, however containers may burn.

FIRE INCOMPATIBILITY

- None known.

continued...

QUIKCOTE VELVET "DADDO" FINISH

Chemwatch GHS Safety Data Sheet
Issue Date: 26-Jul-2013
C554SP

CHEMWATCH 4951-17
Version No:6.1.1.1
CD 2013/2 Page 3 of 7

Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

- Clean up all spills immediately.
- Avoid contact with skin and eyes.
- Wear impervious gloves and safety glasses.
- Use dry clean up procedures and avoid generating dust.

MAJOR SPILLS

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- Control personal contact with the substance, by using protective equipment and dust respirator.
- Prevent spillage from entering drains, sewers or water courses.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Limit all unnecessary personal contact.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Avoid contact with incompatible materials.

SUITABLE CONTAINER

- Multi-ply paper bag with sealed plastic liner or heavy gauge plastic bag.

NOTE: Bags should be stacked, blocked, interlocked, and limited in height so that they are stable and secure against sliding or collapse.

STORAGE INCOMPATIBILITY

- Segregate from, acids.

STORAGE REQUIREMENTS

- Keep dry.
- Store under cover.
- Protect containers against physical damage.
- Observe manufacturer's storage and handling recommendations contained within this MSDS.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

MATERIAL DATA

QUIKCOTE VELVET "DADDO" FINISH:

- None assigned. Refer to individual constituents.

PORTLAND CEMENT: TWA: 10 mg/m³

- for calcium silicate:

containing no asbestos and <1% crystalline silica

ES TWA: 10 mg/m³ inspirable dust

TLV TWA: 10 mg/m³ total dust (synthetic nonfibrous) A4

Although in vitro studies indicate that calcium silicate is more toxic than substances described as "nuisance dusts" is thought that adverse health effects which might occur following exposure to 10-20 mg/m³ are likely to be minimal. The TLV-TWA is thought to be protective against the physical risk of eye and upper respiratory tract irritation in workers and to prevent interference with vision and deposition of particulate in the eyes, ears, nose and mouth.

NOTE: This substance has been classified by the ACGIH as A4 NOT classifiable as causing Cancer in humans.

For calcium oxide:

The TLV-TWA is thought to be protective against undue irritation and is analogous to that recommended for sodium hydroxide.

For aluminium oxide:

The experimental and clinical data indicate that aluminium oxide acts as an "inert" material when inhaled and seems to have little effect on the lungs nor does it produce significant organic disease or toxic effects when exposures are kept under reasonable control.

[Documentation of the Threshold Limit Values], ACGIH, Sixth Edition.

continued...

QUIKCOTE VELVET "DADDO" FINISH

Chemwatch GHS Safety Data Sheet
Issue Date: 26-Jul-2013
C554SP

CHEMWATCH 4951-17
Version No:6.1.1.1
CD 2013/2 Page 4 of 7

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

The concentration of dust, for application of respirable dust limits, is to be determined from the fraction that penetrates a separator whose size collection efficiency is described by a cumulative log-normal function with a median aerodynamic diameter of $4.0 \mu\text{m}$ (+-) $0.3 \mu\text{m}$ and with a geometric standard deviation of $1.5 \mu\text{m}$ (+-) $0.1 \mu\text{m}$, i.e..generally less than $5 \mu\text{m}$.

for chrome(VI) containing substances:

Some jurisdictions require that health surveillance be carried on workers occupationally exposed to inorganic chromium. Such surveillance should emphasise

- demography, occupational and medical history and health advice
- physical examination with emphasis on the respiratory system and skin
- weekly skin inspection of hands and forearms by a "responsible person".

Portland cement is considered to be a nuisance dust that does not cause fibrosis and has little potential to induce adverse effects on the lung.

CALCIUM CARBONATE: TWA: 10 mg/m³

■ For calcium carbonate:

The TLV-TWA is thought to be protective against the significant risk of physical irritation associated with exposure.

ACRYLIC POLYMER:

■ These "dusts" have little adverse effect on the lungs and do not produce toxic effects or organic disease. Although there is no dust which does not evoke some cellular response at sufficiently high concentrations, the cellular response caused by P.N.O.C.s has the following characteristics:

- the architecture of the air spaces remain intact,
- scar tissue (collagen) is not synthesised to any degree,
- tissue reaction is potentially reversible.

Extensive concentrations of P.N.O.C.s may:

- seriously reduce visibility.

PERSONAL PROTECTION

RESPIRATOR

•Particulate. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

EYE

- Safety glasses with side shields; or as required,
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent].

HANDS/FEET

- Barrier cream and • PVC gloves or • Protective gloves eg. Leather gloves or gloves with Leather facing.
- Safety footwear.

OTHER

- Overalls.
- Eyewash unit.

ENGINEERING CONTROLS

■ Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Odourless light grey powder; partly miscible with water.

PHYSICAL PROPERTIES

State	Divided Solid	Molecular Weight	Not Applicable
-------	---------------	------------------	----------------

continued...

QUIKCOTE VELVET "DADDO" FINISH

Chemwatch GHS Safety Data Sheet
Issue Date: 26-Jul-2013
C554SP

CHEMWATCH 4951-17
Version No:6.1.1.1
CD 2013/2 Page 5 of 7

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Melting Range (°C)	Not Applicable	Viscosity	Not Applicable
Boiling Range (°C)	Not Applicable	Solubility in water (g/L)	Partly Miscible
Flash Point (°C)	Not Applicable	pH (1% solution)	Not Available
Decomposition Temp (°C)	Not Available	pH (as supplied)	Not Applicable
Autoignition Temp (°C)	Not Applicable	Vapour Pressure (kPa)	Not Applicable
Upper Explosive Limit (%)	Not Applicable	Specific Gravity (water=1)	Not Available
Lower Explosive Limit (%)	Not Applicable	Relative Vapour Density (air=1)	Not Applicable
Volatile Component (%vol)	Not Applicable	Evaporation Rate	Not Applicable

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

For incompatible materials - refer to Section 7 - Handling and Storage.

Section 11 - TOXICOLOGICAL INFORMATION

Health hazard summary table:

Acute toxicity	Not applicable
Skin corrosion/irritation	Skin Irrit. 2
Serious eye damage/irritation	Eye Dam. 1
Respiratory or skin sensitization	Not applicable
Germ cell mutagenicity	Not applicable
Carcinogenicity	Not applicable
Reproductive toxicity	Not applicable
STOT- single exposure	STOT SE 3
STOT- repeated exposure	Not applicable
Aspiration hazard	Not applicable

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

- The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.

EYE

- If applied to the eyes, this material causes severe eye damage.

SKIN

- This material can cause inflammation of the skin on contact in some persons.
- Products when wet may be quite alkaline and this alkali action on the skin may contribute to cement contact dermatitis by causing drying and defatting of the skin which may be followed by hardening, cracking, development of lesions, possible infections of lesions and penetration by soluble salts.
- The material may accentuate any pre-existing dermatitis condition.

INHALED

- The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.
 - Effects on lungs are significantly enhanced in the presence of respirable particles.
 - Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled.
- If prior damage to the circulatory or nervous systems has occurred or if kidney damage has been sustained, proper screenings should be conducted on individuals who may be exposed to further risk if handling and use of the material result in excessive exposures.

CHRONIC HEALTH EFFECTS

- Long-term exposure to respiratory irritants may result in disease of the airways involving difficult breathing and related systemic problems.
- Cement dust is an allergen with skin contact and/or dust inhalation possibly causing allergic response or even sensitisation responses.

continued...

QUIKCOTE VELVET "DADDO" FINISH

Chemwatch GHS Safety Data Sheet
Issue Date: 26-Jul-2013
C554SP

CHEMWATCH 4951-17
Version No:6.1.1.1
CD 2013/2 Page 6 of 7

Section 11 - TOXICOLOGICAL INFORMATION

TOXICITY AND IRRITATION

■ Not available. Refer to individual constituents.

SKIN

calcium carbonate	GESAMP/EHS Composite List - GESAMP Hazard Profiles	D1: skin irritation/corrosion	0
-------------------	--	-------------------------------	---

Section 12 - ECOLOGICAL INFORMATION

No data

Ecotoxicity

Ingredient	Persistence: Water/Soil	Persistence: Air	Bioaccumulation	Mobility
portland cement	No Data Available	No Data Available	No Data Available	No Data Available
calcium carbonate	No Data Available	No Data Available	No Data Available	No Data Available
acrylic polymer	No Data Available	No Data Available	No Data Available	No Data Available

Section 13 - DISPOSAL CONSIDERATIONS

- Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Management Authority for disposal.
- Bury residue in an authorised landfill.
- Recycle containers if possible, or dispose of in an authorised landfill.

Section 14 - TRANSPORTATION INFORMATION

HAZCHEM:

None (ADG7)

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS: ADG7, IATA, IMDG

Section 15 - REGULATORY INFORMATION

Indications of Danger:

Xi Irritant

POISONS SCHEDULE None

REGULATIONS

Regulations for ingredients

portland cement (CAS: 65997-15-1) is found on the following regulatory lists;

"Australia Exposure Standards", "Australia High Volume Industrial Chemical List (HVICL)", "Australia Inventory of Chemical Substances (AICS)", "OECD List of High Production Volume (HPV) Chemicals"

calcium carbonate (CAS: 471-34-1,13397-26-7,15634-14-7,1317-65-3,72608-12-9,878759-26-3,63660-97-9,459411-10-0,198352-33-9,146358-95-4) is found on the following regulatory lists;

"Acros Transport Information", "Australia Drinking Water Guideline Values For Physical and Chemical Characteristics", "Australia Exposure Standards", "Australia High Volume Industrial Chemical List (HVICL)", "Australia Inventory of Chemical Substances (AICS)", "Australia Quarantine and Inspection Service List of chemical compounds that are accepted solely for use at establishments registered to prepare meat and meat products for the purpose of the Export Control Act 1982", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix C", "Australia Standard for the Uniform Scheduling of Medicines and Poisons"

continued...

QUIKCOTE VELVET "DADDO" FINISH

Chemwatch GHS Safety Data Sheet
Issue Date: 26-Jul-2013
C554SP

CHEMWATCH 4951-17
Version No:6.1.1.1
CD 2013/2 Page 7 of 7

Section 15 - REGULATORY INFORMATION

(SUSMP) - Appendix E (Part 2)", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix F (Part 3)", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6", "Australia Therapeutic Goods Administration (TGA) Substances that may be used as active ingredients in Listed medicines", "CODEX General Standard for Food Additives (GSFA) - Additives Permitted for Use in Food in General, Unless Otherwise Specified, in Accordance with GMP", "FisherTransport Information", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "IMO IBC Code Chapter 17: Summary of minimum requirements", "International Council of Chemical Associations (ICCA) - High Production Volume List", "International Numbering System for Food Additives", "OECD List of High Production Volume (HPV) Chemicals", "Sigma-AldrichTransport Information"

No data for Quikcote Velvet "Daddo" Finish (CW: 4951-17)

No data for Quikcote Velvet "Daddo" Finish (CAS: , Not avail)

Section 16 - OTHER INFORMATION

INGREDIENTS WITH MULTIPLE CAS NUMBERS

Ingredient Name	CAS
calcium carbonate	471- 34- 1, 13397- 26- 7, 15634- 14- 7, 1317- 65- 3, 72608- 12- 9, 878759- 26- 3, 63660- 97- 9, 459411- 10- 0, 198352- 33- 9, 146358- 95- 4

■ Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:
www.chemwatch.net/references.

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: 26-Jul-2013
Print Date: 26-Jul-2013