



Quikcote Victoria Plaster Technology Pty Ltd ABN 76 078 391 545
26–30 Fleet Street Somerton, Victoria 3062
Factory 9303 7791 Fax 9303 7792
Email info@quikcote.com.au Web www.quikcote.com.au

Quikcote Stucco is a cement based, polymer enhanced product used mainly as the final coat or applied finishing coat, after your project has been rendered.

Quikcote Stucco is different than most other applied finishes because of natural products being used in manufacturing process. Being sand and cement based this lets the product absorb and release water retention at will, which will naturally strengthen and produce a superior product.

Quikcote Stucco comes in various colors (samples on request), and is packaged in 20kg bags 3mm course finish..

Quikcote Stucco finish is not like pure acrylic applied finishes, it gives you a natural type faded finish.

Quikcote Stucco can be applied with a trowel and finished off With either a polystyrene float or Perspex floats giving unique finishing effects.

Quikcote Stucco is suitable for:

- Masonary surfaces
- Rendered surfaces
- Cement sheet application, provided it has already been rendered with Quikpatch)
- Also polystyrene applications.

SURFACE PREPARATION

To ensure correct adhesion, surfaces must be suitably flat and clean ie: free of contaminants such as grease, waxes, paint and any oil based substances.

APPLICATION

Quikcote Stucco when mixed should be added to approximately 2 to 3 litres of water using entire 20kg. of product.

Mixing to be done by mixing product to a creamy consistency, let slake for 5 to 10 minutes, and re-drill product, do not add any more water. It will come back wetter when re-drilled.

1: Apply Quikcote Stucco with a steel trowel laying tight to wall.

2: Work the product with styrene float to get required finish.

Note: You must a wet edge at all times.

COVERAGE

Depending on surface application, approximately 2 to 4 metres.

IDENTIFICATION

Product Name: Stucco

UN Number: na

Poisons Schedule Number:na

Purpose: Colored applied finish

GUARANTEE:

All products are guaranteed for seven years under *normal conditions.

This product should be used in accordance with directions which are only a guide. Quikcote accepts no responsibility for inappropriate use or faulty workmanship. All mineral earth based aggregate /course filler based renders and textures will contain a low percentage of carbon and/or ferrous contaminants and can occasionally spot the surface. All care is taken in raw material selection to minimize such effects. Quikcote accepts no responsibility for this occasional occurrence.

PHYSICAL DESCRIPTION

Appearance: coloured

Vapor Pressure: na

Specific Gravity: 1.86 @ 25 Degrees Celsius

Flammability: na

Solubility: Water Soluble

HAZARDOUS INGREDIENTS

Sand >50%

Cement >30%

Pigment = variable

Proprietary additives (non hazardous) <20%

Remaining products are not deemed to be hazardous and are commercially confidential.

HEALTH HAZARD & FIRST AID INFO

- **SKIN CONTACT:**

Prolonged exposure may cause skin irritation:
Wash off with water.

- **EYE CONTACT:**

May cause pain: Irrigate with water for at least 15 min.

- **IF SWALLOWED:**

Single dose oral toxicity is low BUT do not induce vomiting. DO call a doctor and transport to emergency facility for further instructions.

- **IF INHALED:**

Prolonged inhalation may cause irritation:

Ensure adequate ventilation.

- **ENSURE SAFETY GLASSES ARE WORN FOR EYE PROTECTION**

- **GLOVES, BOOTS AND OVERALLS SHOULD BE WORN FOR PROLONGED CONTACT.**

SPILLS: SMALL SPILLS: SHOULD BE MOPPED UP OR SOAKED UP . LARGE SPILLS: SHOULD BE CONTAINED. AVIOD SPILLAGE INTO WATER SUPPLIES.

CLEAN UP

Warm water clean –up prior to drying.