



Quikcote Victoria Plaster Technology Pty Ltd ABN 76 078 391 545  
26–30 Fleet Street Somerton, Victoria 3062  
Factory 9303 7791 Fax 9303 7792  
Email [info@quikcote.com.au](mailto:info@quikcote.com.au) Web [www.quikcote.com.au](http://www.quikcote.com.au)

**Quikcote Velvet Finish** is a cementitious based acrylic finish, providing a fine surface profile for long term weather proofing of exterior surfaces.

**Quikcote Velvet Finish** is manufactured using the highest quality products giving strength, durability and long term resistance to weathering.

**Quikcote Velvet Finish** is very workable Skimcote product, with ease of application and finishing. It can be used not only for new surfaces but is ideal for resurfacing, Patching and rejuvenation of existing surfaces.

**Quikcote Velvet Finish** is suitable for:

- Rendered Brickwork
- Concrete Surfaces (provided they are rendered)
- Aerated Blocks (AAC Blocks)(Provided They Are Rendered)
- Pre-cast panel (provided they are rendered)
- Concrete Block & Bricks (Provided They Are Rendered)

#### **SURFACE PREPARATION**

To ensure correct adhesion, surfaces must be suitably Flat and clean ie: free of contaminants such as grease, Waxes, paint and any oil based substances.

#### **APPLICATION**

Apply 1<sup>st</sup> Coat with a steel trowel 1 – 2mm Thickness,  
After approx 10 to 15 min apply 2<sup>nd</sup> coat over the wall  
To achieve a desired flat smooth finish.  
(Note: Quikcote strongly advises that this product be applied  
By a Qualified Tradesman)

#### **COVERAGE**

8 to 10 m<sup>2</sup> per bag depending on surface per 15kg bag.

#### **TECHNICAL DATA**

Specific Gravity: 1.86 kg/lit  
Odor: Nil  
Base: Cement  
Surface Finish: Medium  
Weather Resistance: High  
PH: 11  
Viscosity of Mix: (CPS) 95,000

#### **CLEAN UP**

Warm water clean –up prior to drying.

#### **GUARANTEE:**

All products are guaranteed for seven years under  
\*normal conditions.

This product should be used in accordance with directions which are only a  
guide. Quikcote accepts no responsibility for inappropriate use or faulty  
workmanship. All mineral earth based aggregate /course filler based renders and  
textures will contain a low percentage of carbon and/or ferrous contaminants

and can occasionally spot the surface. All care is taken in raw material selection  
to minimize such effects. Quikcote accepts no responsibility for this occasional  
occurrence.

#### **IDENTIFICATION**

Product Name: Velvet Finish.  
UN Number: na  
Poisons Schedule Number: na  
Purpose: Surface Coating

#### **PHYSICAL DESCRIPTION**

Appearance: White or Grey  
Vapor Pressure: na  
Specific Gravity: 1.86 @ 25 Degrees Celsius  
Flammability: na  
Solubility: Water Soluble

#### **HAZARDOUS INGREDIENTS**

Cement >30%  
Proprietary additives (non hazardous) <70%  
**Remaining products are not deemed to be hazardous and  
are commercially confidential.**

#### **HEALTH HAZARD & FIRST AID INFO**

- **SKIN CONTACT:**  
Prolonged exposure may cause skin irritation:  
Wash off with water.
- **EYE CONTACT:**  
May cause pain: Irrigate with water for at least  
15 min.
- **IF SWALLOWED:**  
Single dose oral toxicity is low BUT do not  
induce vomiting. DO call a doctor and transport  
to emergency facility for further instructions.
- **IF INHALED:**  
Prolonged inhalation may cause irritation:  
Ensure adequate ventilation.
- **ENSURE SAFETY GLASSES ARE WORN FOR EYE  
PROTECTION**
- **GLOVES, BOOTS AND OVERALLS SHOULD BE  
WORN FOR PROLONGED CONTACT.**  
**SPILLS: SMALL SPILLS: SHOULD BE MOPPED UP OR  
SOAKED UP . LARGE SPILLS: SHOULD BE CONTAINED.  
AVIOD SPILLAGE INTO WATER SUPPLIES.**